

ECO Grandis, FSC

A grade



B grade



Plantation forest grown hardwood from FSC certified forest. Lumber is sawn from butt logs that have a high proportion of clear lumber. Kiln dried using low temperature, appearance, kiln schedules that include a stress relieving and colour equalizing sequence.

Wood is easily machinable for components, turnings, and mouldings. Easily glueable for laminated and jointed components.

Lumber is highly suitable for hardwood furniture, panel doors, outdoor furniture, and laminated parts.

Graded and trimmed: End splits max 150mm, with ends trimmed to remove any excessive splitting, no excessive distortion, twist and crook that preclude normal machining removed.

Kiln dried MC is 8~ 10%

Grade A: max 1 ~ 2 knots ,max 20mm sound & tight. Grade B: 2~ 5 knots max 25mm.

Condition: Kiln dried, RS

Grade: A grade and B grade, packaged separately, approx 50% each

Sizes: thickness: 21, 25,32mm Width: 75mm and wider, max 5% 55mm,heavy 75&100mm widths.

Lengths: 1.8m and longer, max 3.0m, packaged to length, heavy 2.7~ 3.0m lengths.

Components: Available as CTL rough sawn and surfaced and profiled solid parts, also laminated and finger jointed blanks and components can be manufactured.

CTL surfaced clear components



Laminated and ripped to width CTL componets



KDRS A grade

KDRS A grade



KDRS B Grade

KDRS B Grade

